

## Overview standard delivery programm

	型號	安裝介面	反應時間 0~90% in mS	額定流量 $\Delta 70\text{bar}$ l/min	操作壓力 bar	驅動電流 mA	內建電子卡		一般應用
							電壓 >	輸入 mA or V	
	HVM 061	CETOP 03	3.5	0.4-8	0-210	200	24	$\pm 10\text{V}$ 0-20 mA	先進程序化技術機械
	HVM 062	CETOP 03	3	5-30	5-315	200	24	$\pm 10\text{V}$ 0-20 mA	紡織機械加工工具機
	HVM 063	CETOP 03	5	0.5-20	5-210	300	24	$\pm 10\text{V}$ 0-20 mA	試驗機械 厚薄間隙控制機械
	HVM 064	CETOP 03	4	5-40	5-210	300	24	$\pm 10\text{V}$ 0-20 mA	液壓-軸控制
	HVM 056 HVM 057	CETOP 05	5	5-50	5-315	300	24	$\pm 10\text{V}$ 0-20 mA	試驗機械
	HVM 067	CETOP 05	5	10-120	5-315	300	24	$\pm 10\text{V}$ 0-20 mA	沖孔機械 連續快速營養機械
	HVM 071	CETOP 05	5	10-120	5-315	300	24	$\pm 10\text{V}$ 0-20 mA	壓模成形機械
	HVM 090	CETOP 05	7	5-70	5-315	300	24	$\pm 10\text{V}$ 0-20 mA	精密折彎機械 壓平校直機械
	HVM 188	CETOP 08 Special	10	80-400	10-315	300			沖床機械
	HVM 106	CETOP Schneider	10	10-180	5-420	300			試驗機械 厚薄間隙控制機械
	HVM 107	CETOP Schneider	10	30-300	5-420	300			試驗機械 厚薄間隙控制機械
	HVM 108	CETOP Schneider	10	80-720	5-420	300			沖床機械 試驗機械